



Heavy-duty — Excellent Durability and Reliability — SafeLand Quality

WQ-S SERIES



WQ-S

Stainless Steel SS304 SS316 SS316L
water and acid
Channel Impeller Series



Stainless Steel Sewage Wastewater Submersible Pump

FEATURES:

- Precision casting with the use of an advanced stainless investment casting method, produces the highest quality with a smooth surface finish.
- Standard accessories include : cable with an epoxy resin sealed water-resistant cable base, Auto-cut motor protector, dual mechanical seals and oil seal design.
- Chemically protected Viton O-rings to handle acidic and corrosive fluids.
- Pump hydraulic body made of corrosion resistant SUS316L SUS316 SUS304 stainless steel material, to handle low pH value chemical media and/or seawater applications.
- SUS316L is better than SUS304& SUS316 in water application of light acid-base.
- pH2~10 (As reference at operating temperature range 0 - 40°C. 60-90°C can make special order)


APPLICATIONS:

- Wastewater treatment in food and wine-making industry.
- Wastewater treatment of acid fluid in gold mining, petroleum industry and dyeing industry.
- Chemicals, low pH, corrosive and sea water applications.

SPECIFICATIONS

Item		Description
Limits of Use	Liquid Temp.	0~40°C (32~104°F) (60°C -90°C special order)
	Applications	Corrosive • Food • Processing Liquids
Type	Frequency	50Hz
	Motor	2P(3000rpm) • Dry Motor
	Insulation	Class F
	Protection	IP68
	Protector	Auto-cut (0.5HP 3Ø~10HP) • MTS & MS(15~20HP)
	Bearing	Ball type
	M.seal	Double M.seals (alloy to silicon)
	Impeller	Chanel impeller
	Cable	VCT or H07RN-F
Optional	Pump can be customized to fit specifications	

SUS304 SUS316 SUS316L WQ-SG SERIES CONSTRUCTION



item	parts	Material
1	ring	SUS304 / SUS316 /SUS316L
2	screw	SUS304 / SUS316 /SUS316L
3	capacitor cover	SUS304 / SUS316 /SUS316L
4	upper cover	SUS304 / SUS316 /SUS316L
5	bearing	standard component
6	rotor	shaft in pump by SUS304 /SUS316/SUS316L(in motor by
7	motor casing	SUS304 / SUS316 /SUS316L
8	stator core with winding	cold silicon600 /copper wire
9	bearing	standard component
10	oil chamber	SUS304 / SUS316 /SUS316L
11	screw	SUS304 / SUS316 /SUS316L
12	mechanical seal	alloy
13	oil chamber cover	SUS304 / SUS316 /SUS316L
14	oil seal	NBR /viton/ PTFE
15	impeller(chanel impeller)	SUS304 / SUS316 /SUS316L
16	pump body	SUS304 / SUS316 /SUS316L
17	screw	SUS304 / SUS316 /SUS316L
18	base	SUS304 / SUS316 /SUS316L
19	screw	SUS304 / SUS316 /SUS316L
20	Stir	SUS304 / SUS316 /SUS316L



Chanel impeller



STIR

ACCESSORIES :


ELBOW (SUS316L SUS316 SUS304) - GUIDE RAIL SYSTEMS (SUS316L SUS316 SUS304)




PRODUCT NOMENCLATURE

50WQ9-22-2.2S

50	outlet size(mm)
WQ	WQ submersible sewage pump
9	rated flow (m ³ /h)
22	rated head (M)
2.2	rated power (KW)
S	S material SUS304 SUS316 SUS316L

[illegible]

Model	VOLT AGE	Curre nt	Motor power		speed		Outlet	Rated capacity	Rated head	Max capacity	Max head	Impeller passage	N.W
50Hz	V	A	KW	HP	Rpm	pole	inch	m³/h	m	m³/h	m	mm	KG
50WQ10-10-0.75S	380V	1.68	0.75	1	2900	2	2"	10	10	23.71	11.9	20	
50WQ7-15-1.1S	380V	2.64	1.1	1.5	2900	2	2"	7	15	27.28	16.48	20	
50WQ15-15-1.5S	380V	3.85	1.5	2	2900	2	2"	15	15	33.34	20.1	20	
50WQ15-20-2.2S	380V	5.05	2.2	3	2900	2	2"	15	20	39.55	24.1	20	
50WQ15-25-3S	380V	6.53	3	4	2900	2	2"	15	25	40.25	29.0	20	
50WQ15-32-4S	380V	11.44	4	5.5	2900	2	2"	15	32	46.66	40.9	20	
50WQ15-40-5.5S	380V	12.21	5.5	7.5	2900	2	2"	15	40	48.61	44.5	20	
50WQ20-40-7.5S	380V	15.87	7.5	10	2900	2	2"	20	40	58.96	49.3	20	
50WQ20-50-11S	380V	21.21	11	15	2900	2	2"	20	50	59.15	53.9	20	
50WQ20-55-15S	380V	29.51	15	20	2900	2	2"	20	55	78.91	58.4	20	

[illegible]

Model	VOLT AGE	Curre nt	Motor power		speed		Outlet	Rated capacity	Rated head	Max capacity	Max head	Impeller passage	N.W
50Hz	V	A	KW	HP	Rpm	pole	inch	m³/h	m	m³/h	m	mm	KG
350WQ1000-6-30S	380V	53.86	30	40	980	6	14"	1000	6	1185.13	16.9	90	